

Public Advisory Committee Meeting

Seabrook-Hampton Bridge Project Project No. 15904

November 13, 2018







Agenda



- Welcome and Introductions
- Project Update
 - Public Meeting September 26, 2018
 - Alternatives Analysis Update
 - Vessel Users Meeting October 25, 2018
- Traffic Study Results
- Typical Roadway and Bridge Cross-Sections
- Next Steps
 - Alignment and Bridge Replacement Study
 - PAC, Abutters, Cultural Resources & Public Information Meetings in December & January

Project Update



- Public Informational Meeting Held on September 26, 2018
- Vessel Users Meeting Held on October 25, 2018
- Data Gathering and Collection Existing conditions, environmental, cultural
- Development of Cultural and Environmental Documentation
- Investigated Rehabilitation Alternative
- Conducted Traffic Analysis
- Initiated Bridge Studies Phase
- Preparing for Alignment and Roadway Study

Public Informational Meeting



- Mixed opinions about rehabilitation vs replacement
- Abutters want to meet with the team before the next public meetings
- Questions about historical review process...will it limit options?
- Is there funding for the project?
- Bridge must accommodate traffic & emergency vehicles



About 75 people attended the meeting

Study of Rehabilitation Alternative



- Assessed rehabilitation for current capabilities, long term viability and for serving the purpose/need of project
- Requires significant modifications to carry current design loads, even without widening
- Insufficient capacity for widened roadway
- Providing widened roadway to meet needs of travelling public requires replacement the entire superstructure (all steel girders) and widening of piers
- Geometry of bascule pier restricts ability to update mechanical systems



Typical Bridge Underside

Vessel Users Meeting



- Met on October 25
- Discussed current usage
 - Over 800 lifts per year
 - ▶ 15 Vessels account for ~92% of lifts
 - Continuing to gather additional user information
- Solicited feedback from vessel users. Key concerns provided:
 - Width and height of channel important
 - Users have removed rigging from vessels to avoid requiring lifts
 - Staging construction to allow mobility for channel users
 - Allowing for future dredging equipment



Stated Navigational Clearances per Coast Surveys at MHW

Questions



- Before moving to the next section, please ask any questions you may have regarding
 - Public Informational Meeting
 - Rehabilitation Alternative
 - Vessel Users Meeting



Roadway Context



- Community Link and a Gateway into Downtown Hampton Beach
 - Roadway Transition
 - Appropriate Bicycle and Pedestrian Accommodations
 - Traffic Flow and safety
 - Emergency Response Considerations
 - Allows for future connectivity improvements at Dover Avenue Intersection




Looking North Into Hampton

Roadway Cross-Section



- Roadway Element Assessment:
 - Travel Lane
 - Shoulders
 - Sidewalk
- Methodology
 - Scope of Study
 - Evaluation of Existing Conditions
 - Projected Growth and Future Volumes
 - Proposed Conditions Rehabilitation, New Bascule, & New Fixed Bridge
 - Multi-modal Cross-Section Considerations



Looking downward at bascule span

Data Gathering




- NHDOT Automated Traffic Recorder
- Multi-modal Video Turning Movement Counts
- Hampton Beach Master Plan (HBMP) Traffic Data
- Town of Hampton and Rockingham Planning Commission Growth Rates
- Harbor Master and Bridge Lift Logs

30		+
Date Type 5/3/18 PARTY	Audreif MAR	Siriction Vessels
5/3/18 PANY	Merriee IT	IN (
5/4/18 PRANY 5/4/18 PRANY 5/4/18 PRANY	Yellow Bind/Auday our - Mckeilee III Yellow Bind Auday mare/ ouckeilee III	Ta 3
5/5/18 Parts 5/5/18 Parts 5/5/18 Parts	Yellowbuill Mendee TI Mendee TI	Out 1
5/5/18 Sport	See Castle Nudry Mac	In / In / In
5/5/18 Party 5/5/18 Party 5/5/18 Party	Vellowbind Whole Star	In , , , , , , , , , , , , , , , , , , ,
5/6/18 Parts	Tracey Rome / Minile III	Out 3-
5/4/18 Part 5/6/18 Part 5/4/18 Part	Nuder Mae- Mender III Traces None-	In 1 In 1
5/4/18 Party	White Star Vellowbird	In (
5/7/18 YARTY	YELLOW BIRD + MERRILEE #	OUT 2

Existing Conditions




- 15,800 Average Daily Traffic (peak)
- 9,800 Annual Average Daily Traffic
- 700-800 Vehicles Per Hour
- 30 Bicycles during Peak Hour
- 50 Pedestrians during Peak Hour
- 5 Minute Bridge Lift
 - Lifts occur on average 8-10 times per day during summer months



Typical Cross Sections




- Elements of Design Roadway Cross Section
- Existing conditions shown



Typical Cross Sections



• Elements of Design – Roadway Cross Section




Roadway Cross Sections



- Preferred Lane Width = 11'
 - Meets Design Vehicles
 - Goal for Calmer Traffic Speeds
- Lane Number Determination
 - Traffic Design Considerations
 - ▶ 1,500 Vehicles Per Hour Lane Capacity
 - 2, 3, & 4 Lane Options


Existing Conditions





Roadway Cross Sections





Existing Conditions









- Average bridge lift cycle approximately 5 minutes
- Queue duration 9-10 minutes

Roadway Cross Sections



• Lane Determination – Additional Roadway & Traffic Consideration



- 1 Lane from Ashworth Avenue and
- 1 Lane from Ocean Boulevard

Receiving Condition - Ocean Boulevard - 2 Lanes

Roadway Cross Section



- Considerations
 - Traffic Distribution Does Not Support 3-Lane Cross Section
 - Lane Balance and Heavy U-Turn at Ashworth Avenue and Ocean Boulevard
 - 4-Lane Cross Section Provides Minimal Benefit in Overall Traffic Operations
 - 4-Lane Cross Section has Potential for Higher Travel Speeds and Reduced Safety
 - > 3-Lane and 4-Lane Cross Sections Create More Challenging Pedestrian Crossing
 - Future Bridge Configuration has Potential to Reduce Bridge Lifts by 80% or more
 - ▶ Future Peak Hour Volume Can Easily be Accommodated with 2-Lane Cross Section
 - Access for Emergency Vehicles Improved by Improved Shoulders, Not Additional Lanes

Questions




- Before moving to the next section, please ask any questions you may have regarding
 - Traffic Analysis
 - Roadway Travel Way





Shoulder Width Considerations



Existing Conditions




















- Shoulder Width Considerations
 - Bicycles require 5' minimum when adjacent to curb, based on State and National Guidelines
 - National Guidelines based on Traffic Volumes Require 6'-8'
 - 2' Cyclists Shy Distance Away from Vertical Elements
 - Debris and Bridge Scuppers Limit Useable Shoulder Width
 - Guidelines recommend 18' Required from Centerline to Curb to allow Emergency/Disabled Vehicles to Pass

















Sidewalk Cross Sections



Sidewalk Width Considerations



Existing Conditions
















Sidewalk Cross Sections



- Sidewalk Width Considerations
 - Hampton Beach Master Plan (HBMP) Goals to Improve Pedestrian and Bicycle Safety & Provide Greater Connectivity to Resources North and South of Bridge
 - Pedestrian Desire Lines on East and West Sides of Bridge
 - Existing At-Grade Pedestrian Crossings of NH Route 1A
 - Opportunities for Mix of Travel Speeds and Activities (Fishing, Biking, Walking)
 - Potential Objects Impact on Accessible Route (Lighting, Signs, Furniture)

Sidewalk Cross Sections Options





Questions



- This concludes our presentation, please ask any questions you may have regarding
 - Bicycle and Pedestrian Analysis
 - Roadway Shoulders and Sidewalks
 - Project process and next steps



Next Steps



- Continue Development of Alignment and Profile Study
- PAC Meeting December 4, 2018
 - Review alignments and profiles for Replacement Alternatives
 - ▶ Further assessment of Rehabilitation Alternative
- Next Public Involvement Meeting in January 2019.
 Meeting moved to accommodate additional Meetings with PAC, Vessel Owners and Abutters. Will provide updates on:
 - Provide updates on Historic Review process
 - Update on Rehabilitation Alternative
 - Update on alignments and profiles for Replacement Alternatives

Project Development Process



PRELIMINARY DESIGN PROJECT SCHEDULE













Project Development Process



- Complete study of all alternatives and select a Preferred Alternative 2019
 - Followed by Public Meeting to get input from Towns and Users
- Final Design of Preferred Alternative
 - Detailed design plans
 - Environmental Permitting
 - Secure necessary property rights
- Project is scheduled at Advertise in FFY 2023
- Current programmed construction cost of \$28 M
 - (Assumes a fixed structure replacement)
- Construction anticipated to span over several years beginning in 2024